

## Compa II – Modular structure for high versatility.



### Highlights

- > Large label rolls with a diameter up to 200 mm
- > Simplest operating and maintenance
- > Graphic display with white background lighting
- > Serial, parallel, LAN and USB port
- > 2 x USB host for connection of USB keyboard/USB stick
- > Insertion for Compact Flash card
- > Stand-alone mode

### Options

- > WLAN 802.11 b/g interface
- > Rotation cutter unit
- > Dispenser unit
- > Dispenser I/O
- > Internal rewinder
- > External label rewinder

### Guillotine cutter unit



### Dispenser unit



### External label rewinder



	Compa II 103/8 T	Compa II 104/8	Compa II 106/12	Compa II 106/24	Compa II 108/12 T	Compa II 162/12	Compa II 162/12 T
<b>Printing</b>							
Print resolution	203 dpi	203 dpi	300 dpi	600 dpi	300 dpi	300 dpi	300 dpi
Print speed (max)	200 mm/s	200 mm/s	200 mm/s	150 mm/s	200 mm/s	150 mm/s	150 mm/s
Print width (max)	104 mm	104 mm	105.7 mm	105.6 mm	108.4 mm	162.6 mm	162.6 mm
Passage width (max)	116 mm	116 mm	116 mm	116 mm	116 mm	176 mm	176 mm
Printhead	Flat Type <sup>1</sup>	Flat Type <sup>2</sup>	Flat Type <sup>2</sup>	Flat Type <sup>2</sup>	Flat Type <sup>1</sup>	Flat Type <sup>2</sup>	Flat Type <sup>1</sup>
<b>Labels</b>							
Adhesive labels, continuous labels	rolls or fan-fold: paper, cardboard, textile, synthetics						
Material weight	max 220 g/m <sup>2</sup> (larger on demand)						
Label width (min)	12 mm	12 mm	12 mm	12 mm	12 mm	50 mm	50 mm
Label height Standard Cutter mode/dispenser mode	min 5 mm min 25 mm						
Label height	6000 mm	6000 mm	3000 mm	750 mm	3000 mm	2000 mm	2000 mm
Roll diameter internal unwinder internal rewinder	max 200 mm max 145 mm (option)						
Core diameter	40 mm / 75 mm (option)						
Winding	outside or inside						
Label sensor	below transmission and reflexion						
<b>Transfer Ribbons</b>							
Ink	outside or inside						
Core diameter	25.4 mm / 1"						
Roll diameter	max Ø 80 mm						
Length	max 300 m						
Width	max 110 mm . max 170 mm (Compa II 162)						
<b>Fonts</b>							
Font types	6 bitmap fonts   8 vector fonts/TrueType fonts   6 proportional fonts   more fonts on demand						
<b>Bar Codes</b>							
1D bar codes	CODABAR, Code 128, Code 2/5 interleaved, Code 39, Code 39 extended, Code 93, EAN 13, EAN 8, EAN ADD ON, GS1-128, Identcode, ITF 14, Leitcode, Pharmacode, PZN 7 Code, PZN 8 Code, UPC-A, UPC-E						
2D bar codes	Aztec Code, CODABLOCK F, DataMatrix, GS1 DataMatrix, MAXICODE, PDF 417, QR Code						
GS1 bar codes	GS1 DataBar Expanded, GS1 DataBar Limited, GS1 DataBar Omnidirectional, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Truncated						
<b>Dimensions</b>							
width x height x depth	242 x 274 x 446 mm	242 x 274 x 446 mm	242 x 274 x 446 mm	242 x 274 x 446 mm	242 x 274 x 446 mm	302 x 274 x 446 mm	302 x 274 x 446 mm
<b>Weight</b>							
Weight	10 kg	10 kg	10 kg	10 kg	10 kg	14 kg	14 kg
<b>Interfaces</b>							
Serial	RS-232C (max 115,200 baud)						
Parallel	SPP						
USB	2.0 High Speed Slave						
Ethernet	10/100 Base T, LPD, RawIP-Printing, DHCP, HTTP, FTP						
2 x USB Master	connection for external USB keyboard and USB stick						
WLAN (option)	module 802.11 b/g/n WEP, WPA, WPA-PSK, WPA2, WPA2-PSK, EAP						
<b>Operating Conditions</b>							
Nominal voltage	110 ... 230 V AC / 50 ... 60 Hz						
Power	275 VA						
Nominal current	2.5 A						
Operating temperature	5 ... 35 °C						
Relative humidity	max 80 % (non-condensing)						

<sup>1</sup> = Flat Type for thermal direct . <sup>2</sup> = Flat Type for thermal transfer



Local retailer

De Koningh Coding & Labeling BV  
Postbus 137, 6920 AC Duiven  
Geograaf 8, 6921 EW Duiven  
Tel. +31 (0)26 741 00 00  
Fax. +31 (0)26 741 00 99  
info@dekoningh.nl - www.dekoningh.nl